



#### Touchless biometric facial recognition

#### Time & Attendence and Access Control Terminal



Face Verification



Card Verification



Proactive Facial Recognition



Speedy Recognition



empeo certified




4.3-inch
Touch Screen

#### **Features**

- Enhanced Visible Light Facial Recognition
- Recognition distance: 0.3 2 meters
- Better hygiene with touchless identification and face mask detection
- Anti-spoofing algorithm against print attack (laser, color and B/W photos), videos attack and 3D mask attack
- Multiple verification methods: Face / Password / Card (Proximity Card 125KHz)
- Communication mode: TCP /IP, RS232, RS485, Wiegand in /out
- Backup rechargeable battery
- empeo certified product

# **Working Application**



# **Specification**

Display	4.3-inch Touch Screen
Face Capacity	500
User Capacity	1,000
Card Capacity	1,000 ( Proximity Card 125KHz )
Transactions	150,000
Communication	TCP/IP, USB Host
Hardware	1GHz Dual-Core CPU, 256MB RAM / 512MB ROM, 1MP Binocular
Access Control Interface	Camera 3rd Party Electric Lock, Door Sensor, Exit Button
Facial Recognition Speed	≤1s
Power Supply	12V 1.5A
Working Humidity	20% to 80%
Working Temperature	0°C to 45°C
Standard Functions	ADMS, Work Code, DST, Self-service Query, Automatic Status Switch, T9
	Input, Camera, 9-digit User ID, Multiple Verification Methods, Bell Scheduling
Dimensions (W*H*D)	130 * 119 * 28 (mm) / 130*119*55 (mm)

### Dimensions (mm)

